

# SAFETY DATA SHEET

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product Code: GLOSSY

Product Name: GLOSSY COLOR SERIES

MARKETED BY: DESIGN MASTER color tool, inc.

ADDRESS: P.O. Box 601, Boulder, CO 80306

EMERGENCY PHONE: 303-623-5716

INFORMATION PHONE: 800-525-2644

Product Use: Gloss color finish spray

## 2. HAZARDS IDENTIFICATION

### CLASSIFICATION

Flammable aerosol	1
Gas under pressure	Liquefied gas
Acute Toxicity - Inhalation	4
Skin Corrosion/Irritation	3
Eye Damage/Irritation	2B



**SIGNAL WORD:** Danger

### Hazard Statements

Extremely flammable aerosol  
Contains gas under pressure; may explode if heated  
Causes mild skin irritation  
Causes eye irritation  
Harmful if inhaled

### Precautionary Statements

Keep away from heat/sparks/open flames/hot surfaces – No smoking  
Do not spray on an open flame or other ignition source.  
Pressurized container – Do not pierce or burn, even after use  
Avoid breathing dust/fume/gas/mist/vapors/spray  
Wash hands thoroughly after handling  
Use only outdoors or in a well-ventilated area  
Call a POISON CENTER or doctor/physician if you feel unwell  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing  
If skin irritation occurs: Get medical advice/attention  
If eye irritation persists: Get medical advice/attention  
Protect from sunlight. Store in a well ventilated place

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Percent
ACETONE	67-64-1	42.00
PROPANE	74-98-6	17.00
ISOBUTYL ACETATE	110-19-0	15.90
ISOPROPYL ALCOHOL	67-63-0	4.20
ETHYL 3-ETHOXYPROPRIONATE	763-69-9	2.60
PETROLEUM DISTILLATE	64742-89-8	2.00
PROPYLENE GLYCOL METHYL ETHER ACETATE	108-65-6	1.50

### 4. FIRST AID MEASURES

**INHALATION:** Remove to fresh air. Administer oxygen if needed. Apply artificial respiration if breathing has stopped. Get medical attention.

**EYE CONTACT:** Wash immediately with large volumes of fresh water for at least 15 minutes. Get medical attention.

**SKIN CONTACT:** Wipe off with a towel. Wash with soap and water. Get medical attention if irritation persists.

**INGESTION:** Not a likely route of exposure.

**Most important symptoms/effects, acute and delayed:** Repeated exposure may cause skin dryness or cracking. May cause drowsiness or dizziness.

**Indication of immediate medical attention and special treatment needed:** None known.

### 5. FIRE FIGHTING MEASURES

**Suitable and unsuitable extinguishing media:** Foam, Alcohol foam, CO<sub>2</sub>, Dry chemical, Water fog. Water spray may be ineffective.

**Specific hazards arising from the chemical:** Closed containers may explode from internal pressure build-up when exposed to extreme heat and discharge contents. Liquid content of container will support combustion. Overexposure to decomposition products may cause a health hazard. Symptoms may not be readily apparent. Obtain medical attention. Hazardous decomposition products include carbon dioxide, carbon monoxide, and other toxic fumes.

**Special equipment and precautions for fire-fighters:** Water may be used to cool containers to prevent pressure buildup and explosion when exposed to extreme heat. Wear goggles and use self-contained breathing apparatus. If water is used, fog nozzles are preferred.

### 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment, and emergency procedures:** Avoid breathing vapors. Ventilate area. Remove all sources of ignition.

**Methods and materials for containment and cleaning up:** Clean up with absorbent material and place in closed containers for disposal.

## 7. HANDLING AND STORAGE

**Precautions for safe handling:** Do not puncture or incinerate (burn) cans. Do not stick pins, nails, or any other sharp objects into opening on top of can. Do not spray in eyes. Do not take internally. See product label for additional information.

**Conditions for safe storage, including any incompatibilities:** Store and use in cool, dry, well-ventilated areas. Do not store above 120 F.

## 8. EXPOSURE CONTROL/PERSONAL PROTECTION

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
ACETONE 67-64-1	PEL-TWA: 750 ppm	TLV-TWA 500 ppm TLV-STEL 750 ppm	
PROPANE 74-98-6	Not established	TWA: 1000 ppm	
ISOBUTYL ACETATE 110-19-0	PEL: 150 ppm	TLV: 150 ppm	
ISOPROPYL ALCOHOL 67-63-0	PEL-TWA: 400 ppm PEL-Ceiling: Not determined	TLV-TWA: 200 ppm TLV-STEL: 400 ppm	
ETHYL 3-ETHOXYPROPIONATE 763-69-9			TWA: 50 ppm (Eastman) STEL: 100 ppm (Eastman)
PETROLEUM DISTILLATE 64742-89-8	PEL-TWA: 500 ppm; PEL-Ceiling: Not determined	TLV-TWA: 400 ppm TLV-STEL: 500 ppm	
PROPYLENE GLYCOL METHYL ETHER ACETATE 108-65-6	Not established	Not established	

**Appropriate engineering controls:** Ventilation should be sufficient to prevent inhalation of any vapors. General dilution and/or local exhaust ventilation in volume to keep PEL/TLV of most hazardous ingredient below acceptable limit and lcl below stated limit.

### Individual protection measures:

**Respiratory protection:** None under normal use. Avoid breathing vapors. In restricted areas, use approved chemical/mechanical filters designed to remove a combination of particles and vapor. In confined areas, use an approved air line respirator or hood. Self-contained breathing apparatus is required for vapor concentrations above PEL/TLV limits. **Protective gloves:** None under normal use. Use solvent-resistant for prolonged or repeated contact.

**Eye protection:** None under normal use. However, use of safety glasses with splash guards or full face shield should be used if indicated.

**Other protective clothing or equipment:** None under normal use. However, use of solvent-resistant aprons or other clothing is recommended. Eye washes and safety showers in the workplace are recommended.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:** Aerosol product

**Odor:** Pleasant

<b>Vapor Pressure:</b> Not determined <b>Vapor Density:</b> Heavier than air <b>Density:</b> Not determined <b>Freezing point:</b> Not determined <b>Boiling point:</b> Not determined <b>Evaporation rate:</b> Slower than ether <b>Explosive Limits:</b> Not applicable  <b>Autoignition temperature:</b> Not determined	<b>Odor threshold:</b> Not determined  <b>pH:</b> Not applicable <b>Melting point:</b> Not determined <b>Solubility:</b> Not determined <b>Flash point:</b> Not determined <b>Flammability:</b> Level 2 Aerosol <b>Partition coefficient (noctanol/water):</b> Not determined  <b>Decomposition temperature:</b> Not determined
<b>Viscosity:</b> Not determined	

**10. STABILITY AND REACTIVITY**

**Reactivity:** Not reactive under normal conditions of use.

**Chemical stability:** Stable under normal storage and handling conditions.

**Possibility of hazardous reactions:** None known.

**Incompatible materials:**

Acids, Bases, Strong oxidizing agents

**Hazardous decomposition products:**

Carbon dioxide, carbon monoxide, smoke, fumes, and other products of incomplete combustion.

**11. TOXICOLOGICAL INFORMATION**

Long-term toxicological studies have not been conducted for this product.

**12. ECOLOGICAL INFORMATION**

Long-term ecological studies have not been conducted for this product.

**13. DISPOSAL CONSIDERATIONS**

Dispose of in accordance with local, state, and federal regulations. Before attempting clean up, refer to other sections of this document for hazard cautionary information.

**14. TRANSPORT INFORMATION**

By land: DOT Proper Shipping Name: None required per 49 CFR 173.306(i) for products that conform to the Limited Quantity provisions. Commodity shipping description: Paint, NOI

By water: DOT & IMDG Proper Shipping Name: UN1950, Aerosols, 2.1, LTD QTY

By air: DOT & IATA Proper Shipping Name: UN1950, Aerosols, flammable, 2.1, LTD QTY (packing instruction Y203 applies)

**15. REGULATORY INFORMATION**

All ingredients are either listed on the TSCA inventory or are exempt.

This product can expose you to chemicals including those listed below, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

HEXONE, METHYL ISOBUTYL KETONE 108-10-1 Carcinogen, Reproductive toxicant

## 16. OTHER INFORMATION

This Safety Data Sheet applies to the following items: Glossy Red 614, Glossy Easel Green 616, Glossy Black 625, Glossy White 626

Date revised: 2020-03-10

Revision 1

Date Printed: 2020-03-10

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. BECAUSE THE INFORMATION CONTAINED HEREIN MAY BE APPLIED UNDER CONDITIONS BEYOND OUR CONTROL, WE ASSUME NO RESPONSIBILITY FOR ITS USE.